

02.08

Multiprime

PRODUCT DESCRIPTION AND USES

Multiprime is a single pack thixotropic paint for application to steel, timber and fibreglass surfaces both above and below the waterline.

Multiprime has excellent touch up properties and may be used as a suitable tie coat.

PHYSICAL PROPERTIES

Colour/Texture	Grey/matt
Volume Solids	28%
Product Density	1.2kg/litre
Drying Time (25°C)	Touch Dry: 20 minutes Hard Dry: 3 hours
Recoat Time (25°C)	Minimum: 4 hours
Flash point	4°C

SURFACE PREPARATION

Surface to be painted must be free of all dirt, grease, oil, loose and flaking paint and any other contaminants.

APPLICATION DATA

Multiprime can be applied directly to properly prepared timber, fibreglass and steel surfaces. Product designed for application by airless spray, brush or roller.

Airless Spray	Line Pressure: 120-150 Bar Tip Size: 0.533-0.787mm Fan Angle: 65-80°
Recommended D.F.T	40 microns
Recommended W.F.T	140 microns
Theoretical Spreading Rate	7-8m ² /litre
Thinners/Cleaners	6.01 Transmarine Single Pack Thinners

HEALTH AND SAFETY

Irritant	Avoid contact with skin and eyes. Avoid breathing vapour or sanding dust. When using this product it is recommended that full overalls, gloves, face mask and goggles be worn. Store container in a safe place when not in use. Do not burn container.
----------	--

FIRST AID**EYES**

Flush with water for at least 15 minutes and seek medical advice.

SKIN

Wash contact areas with soap and water. Remove all contaminated clothing, and seek medical advice. Do not scrub.

INHALATION

Remove patient from further exposure, and keep patient warm and comfortable.

INGESTION

Do not induce vomiting. Rinse mouth with water. Seek medical advice as soon as possible.

TRANSPORTATION AND DISPOSAL

Class

3

Hazchem Code

•3YE (3); •3Y

UN No

1263

Packing Group No

II

Fire Extinguishing Media

CO₂, Foam, Dry Chemical

Fire Fighting Procedure

Fire fighters should wear self contained breathing apparatus. Fight fire from a protected location as product may explode on heating. The vapours are heavier than air, so may travel along the ground to accumulate in low areas. Fire may flash back along vapour trail, and can also react with oxidising agents.

Spills should be cleaned up immediately by using sand or other non-flammable absorbent materials. Ensure material does not enter waterways.

Dispose of empty containers in accordance with local by laws.

OTHER INFORMATION

This product may be used for a wide variety of surfaces. If the surface you propose to paint is not referred to, contact Protective Paints Technical Department for classification.

For further technical information please phone 0800 724 684.

RELIABILITY OF INFORMATION

All statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed. Since Protective Paints Ltd has no control over product application, purchasers and users must confirm the suitability of our products under their conditions to meet their own requirements.

ISSUE NUMBER: 02.08 (V2)

ISSUE DATE: 25 July 2013