



# PROTECTIVE

PAINTS

Protective Paints Limited, 14B Arwen Place, East Tamaki, PO Box 204293, Highbrook Postal Centre, Manukau 2161  
Ph: (09) 274 5606 Ph: 0800 724 684 Fax: (09) 274 0940 Email: reception@propaints.co.nz Website: www.propaints.co.nz

## 0320

### Primer Undercoat

---

#### PRODUCT DESCRIPTION AND USES

Primer Undercoat is a single pack primer undercoat designed especially for marine use where anti-corrosive properties are not required such as timber, plywood and fibreglass. Primer Undercoat has excellent sealing, filling and sanding properties essential for a preparation coat.

NB: Not recommended for continuous immersion.

---

#### PHYSICAL PROPERTIES

Colour/Texture	Off White/matt
Volume Solids	56%
Product Density	1.59kg/litre
Drying Time (25°C)	Touch Dry: 30 minutes Hard Dry: 8-10 hours
Recoat Time (25°C)	Minimum: 8 hours
Flash point	31°C

---

#### SURFACE PREPARATION

Ensure areas to be primed are free of salt, dust, grease and other contaminants.

---

#### APPLICATION DATA

Primer Undercoat may be applied directly to timber and fibreglass surfaces above the waterline or onto a suitable anti-corrosive primer onto steel above the waterline.

Can be applied by brush, roller or airless spray.

Airless spray	Line Pressure: 110-140 Bar Tip Size: 0.432-0.482mm
Recommended D.F.T	40 microns
Recommended W. F.T	70 microns
<b>Theoretical Spreading Rate</b>	10-12m <sup>2</sup> /litre
Thinners/Cleaners	6.01 Transmarine Single Pack Thinners

---

#### HEALTH AND SAFETY

Irritant

Avoid contact with skin and eyes. Avoid breathing vapour or sanding dust.  
When using this product it is recommended that full overalls, gloves, face mask and goggles be worn. Store container in a safe place when not in use. Do not burn container.

---

**FIRST AID****EYES**

Flush with water for at least 15 minutes and seek medical advice.

**SKIN**

Wash contact areas with soap and water. Remove all contaminated clothing, and seek medical advice. Do not scrub.

**INHALATION**

Remove patient from further exposure, and keep patient warm and comfortable.

**INGESTION**

Do not induce vomiting. Rinse mouth with water. Seek medical advice as soon as possible.

---

**TRANSPORTATION AND DISPOSAL**

## Class

3

## Hazchem Code

•3YE (3); •3Y

## UN No

1263

## Packing Group No

III

## Fire Extinguishing Media

CO<sup>2</sup>, Foam, Dry Chemical

## Fire Fighting Procedure

Fire fighters should wear self contained breathing apparatus. Fight fire from a protected location as product may explode on heating. The vapours are heavier than air, so may travel along the ground to accumulate in low areas. Fire may flash back along vapour trail, and can also react with oxidising agents.

Spills should be cleaned up immediately by using sand or other non-flammable absorbent materials. Ensure material does not enter waterways.

Dispose of empty containers in accordance with local by laws.

---

**OTHER INFORMATION**

This product may be used for a wide variety of surfaces. If the surface you propose to paint is not referred to, contact Protective Paints Technical Department for classification.

For further technical information please phone 0800 724 684.

**RELIABILITY OF INFORMATION**

All statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed. Since Protective Paints Ltd has no control over product application, purchasers and users must confirm the suitability of our products under their conditions to meet their own requirements.

ISSUE NUMBER: 03.20 (V2)

ISSUE DATE: 12 August 2013