



# PROTECTIVE

PAINTS

Protective Paints Limited, 14B Arwen Place, East Tamaki, PO Box 204293, Highbrook Postal Centre, Manukau 2161  
Ph: (09) 274 5606 Ph: 0800 724 684 Fax: (09) 274 0940 Email: reception@propaints.co.nz Website: www.propaints.co.nz

## 8340-100

### Duralon Alkyd Flat

---

#### PRODUCT DESCRIPTION AND USES

Protective Paints Duralon Alkyd Flat is a single pack oil based coating formulated on a synthetic alkyd resin. Protective Paints Duralon Alkyd Flat is a relatively low odour product used as a finish coat on suitably sealed Gibraltar Board or plaster.

**NB: This product is not recommended for use on high wear surfaces (e.g. doors) as cleaning is difficult.**

---

#### PHYSICAL PROPERTIES

Colour/Texture	White/Flat
Volume Solids	51%
Product Density	1.46kg/litre
Drying Time	Touch Dry: 30 minutes Hard Dry: 6 hours
Recoat Time	12 hours depending on surface and weather conditions
Flash point	31°C

---

#### SURFACE PREPARATION

Ensure all surfaces are thoroughly clean and dry before application. Remove all loose and flaking material, dirt stains and grease.

Unpainted Gibraltar Board or Plaster	Seal using Protective Paints QD Sealer
Previously Painted Gibraltar Board or Plaster	Scuff entire surface to provide an adequate key

---

#### APPLICATION DATA

Protective Paints Duralon Alkyd Flat may be applied by brush, roller, conventional or airless spray.

Recommended D.F.T	40 microns
Recommended W.F.T	80 microns
Theoretical Spreading Rate	12m <sup>2</sup> /litre @ 40 microns D.F.T
Thinners	Rolling/Brushing: R4 (5-10%) Spraying: G5 (15%)

---

#### HEALTH AND SAFETY

Irritant	Avoid contact with skin and eyes. Avoid breathing vapour or sanding dust. When using this product it is recommended that full overalls, gloves, face mask and goggles be worn. Store container in a safe place when not in use. Do not burn container.
----------	---

---

**FIRST AID****EYES**

Flush with water for at least 15 minutes and seek medical advice.

**SKIN**

Wash contact areas with soap and water. Remove all contaminated clothing, and seek medical advice. Do not scrub.

**INHALATION**

Remove patient from further exposure, and keep patient warm and comfortable.

**INGESTION**

Do not induce vomiting. Rinse mouth with water. Seek medical advice as soon as possible.

---

**TRANSPORTATION AND DISPOSAL**

## Class

3

## Hazchem Code

•3YE (3); •3Y

## UN No

1263

## Packing Group No

III

## Fire Extinguishing Media

CO<sub>2</sub>, Foam, Dry Chemical

## Fire Fighting Procedure

Fire fighters should wear self contained breathing apparatus. Fight fire from a protected location as product may explode on heating. The vapours are heavier than air, so may travel along the ground to accumulate in low areas. Fire may flash back along vapour trail, and can also react with oxidising agents.

Spills should be cleaned up immediately by using sand or other non-flammable absorbent materials. Ensure material does not enter waterways.

Dispose of empty containers in accordance with local by laws.

---

**OTHER INFORMATION**

This product may be used for a wide variety of surfaces. If the surface you propose to paint is not referred to, contact Protective Paints Technical Department for classification.

For further technical information please phone 0800 724 684.

**RELIABILITY OF INFORMATION**

All statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed. Since Protective Paints Ltd has no control over product application, purchasers and users must confirm the suitability of our products under their conditions to meet their own requirements.

ISSUE NUMBER: 8340-100 (V2)

ISSUE DATE: 30 July 2013