

875-902

Vinyl Aluminium Sealer

PRODUCT DESCRIPTION AND USES

Vinyl Aluminium Sealer is specifically formulated for use as a seal coat over metal sprayed surfaces. It exhibits excellent adhesion to Zinc and Aluminium Metal Spray and can be overcoated with most types of finishes.

PHYSICAL PROPERTIES

Colour/Texture	Silver/Matt
Volume Solids (mixed)	20%
Mixing Ratio by volume	N/A
Product Density (mixed)	0.88kg/litre
Mixing Ratio by weight	N/A
Dust Dry (20°C, 60RH)	15 minutes
Potlife	N/A
Drying Time	30 minutes
Recoat Time	4 Hours
Flashpoint	12°C

SURFACE PREPARATION

Vinyl Aluminium Sealer is generally applied directly to metal spray. If the surface is contaminated thorough degreasing of the surface will be required.

APPLICATION DATA

Use Brush, Roller, Air/Airless spray and conventional spray.

Recommended D.F.T	20-25 microns
Recommended W.FT	100-125 microns
Theoretical Spreading Rate	8-10m ² /litre
Thinners	AE12 Thinners

HEALTH AND SAFETY

irritant

Avoid contact with skin and eyes. Avoid breathing vapour or sanding dust.
When using this product it is recommended that full overalls, gloves, face mask and goggles be worn. Store container in a safe place when not in Use. Do not burn container.

FIRST AID**EYES**

Flush with water for at least 15 minutes and seek medical advice.

SKIN

Wash contact areas with soap and water. Remove all contaminated clothing, and seek medical advice. Do not scrub.

INHALATION

Remove patient from further exposure, and keep patient warm and comfortable.

INGESTION

Do not induce vomiting. Rinse mouth with water. Seek medical advice as soon as possible.

TRANSPORTATION AND DISPOSAL

Class

3

Hazchem Code

•3YE (3); •3Y

UN No

1263

Packing Group No

II

Fire Extinguishing Media

CO², Foam, Dry Chemical

Fire Fighting Procedure

Fire fighters should wear self contained breathing apparatus. Fight fire from a protected location as product may explode on heating. The vapours are heavier than air, so may travel along the ground to accumulate in low areas. Fire may flash back along vapour trail, and can also react with oxidising agents.

Spills should be cleaned up immediately by using sand or other non-flammable absorbent materials. Ensure material does not enter waterways.

Dispose of empty containers in accordance with local by laws.

OTHER INFORMATION

This product may be used for a wide variety of surfaces. If the surface you propose to paint is not referred to, contact Protective Paints Technical Department for classification.

For further technical information please phone 0800 724 684.

RELIABILITY OF INFORMATION

All statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed. Since Protective Paints Ltd has no control over product application, purchasers and users must confirm the suitability of our products under their conditions to meet their own requirements.

ISSUE NUMBER: 875-902 (V2)

ISSUE DATE: 29 July 2013

bwjb