



PROTECTIVE

PAINTS

Protective Paints Limited, 14B Arwen Place, East Tamaki, PO Box 204293, Highbrook Postal Centre, Manukau 2161
Ph: (09) 274 5606 Ph: 0800 724 684 Fax: (09) 274 0940 Email: reception@propaints.co.nz Website: www.propaints.co.nz

918-919

Prepkote Grey

PRODUCT DESCRIPTION AND USES

Prepkote Grey is designed as an enamel primer normally used as an automotive undercoat primer where relatively fast dry is required. It has good through dry combined with ease of sanding. Normally used under spraying enamels i.e. 755 Dryfast, 800 Equipment Enamel and 762 Spraying Enamel.

PHYSICAL PROPERTIES

Colour/Texture	Grey / Satin Matt
Volume Solids	34% approximately
Product Density	1.26kg/litre
Drying Time	Tack Dry: 15-20 minutes
Recoat Time	2-3 hours
Flash point	4.4°C

SURFACE PREPARATION

Surface to be painted must be clean, well sanded and free of dirt, rust, grease or other contamination. Thinning may be necessary up to 20% with K9, H9 or G5 Thinners.

HEALTH AND SAFETY

Irritant	Avoid contact with skin and eyes. Avoid breathing vapour or sanding dust. When using this product it is recommended that full overalls, gloves, face mask and goggles be worn. Store container in a safe place when not in use. Do not burn container.
----------	--

FIRST AID

EYES	Flush with water for at least 15 minutes and seek medical advice.
SKIN	Wash contact areas with soap and water. Remove all contaminated clothing, and seek medical advice. Do not scrub.
INHALATION	Remove patient from further exposure, and keep patient warm and comfortable.
INGESTION	Do not induce vomiting. Rinse mouth with water. Seek medical advice as soon as possible.

TRANSPORTATION AND DISPOSAL

Class	3
Hazchem Code	•3YE (3); •3Y
UN No	1263
Packing Group No	II

Fire Extinguishing Media
Fire Fighting Procedure

CO², Foam, Dry Chemical

Fire fighters should wear self contained breathing apparatus. Fight fire from a protected location as product may explode on heating. The vapours are heavier than air, so may travel along the ground to accumulate in low areas. Fire may flash back along vapour trail, and can also react with oxidising agents.

Spills should be cleaned up immediately by using sand or other non-flammable absorbent materials. Ensure material does not enter waterways.

Dispose of empty containers in accordance with local by laws.

OTHER INFORMATION

This product may be used for a wide variety of surfaces. If the surface you propose to paint is not referred to, contact Protective Paints Technical Department for classification.

For further technical information please phone 0800 724 684.

RELIABILITY OF INFORMATION

All statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed. Since Protective Paints Ltd has no control over product application, purchasers and users must confirm the suitability of our products under their conditions to meet their own requirements.

ISSUE NUMBER: 918-919 (V2)

ISSUE DATE: 08 August 2013