



PROTECTIVE

PAINTS

Protective Paints Limited, 14B Arwen Place, East Tamaki, PO Box 204293, Highbrook Postal Centre, Manukau 2161
Ph: (09) 274 5606 Ph: 0800 724 684 Fax: (09) 274 0940 Email: reception@propaints.co.nz Website: www.propaints.co.nz

933-001

Murrays Oil Seal

PRODUCT DESCRIPTION

Murrays Oil Seal is a penetrating oil seal/finish designed to provide a hand-rubbed look on interior furniture, trim, panelling etc. It is suitable for garden furniture, BBQ trolleys etc and exhibits very positive drying characteristics. In areas subject to permanent exterior exposure, recoating may be required.

PHYSICAL PROPERTIES

Colour/Texture	Clear/Satin
Volume Solids	41.5%
Product Density	0.86kg/litre
Recoat Time	6-8 hours
Flash point	32°C

SURFACE PREPARATION

Ensure surface is clean, sound and dry.

APPLICATION DATA

Apply by brush, roller, conventional spray, or rag.

Thinners	R4
Theoretical Spreading Rate	6-8m ² /litre depending on surface porosity

HEALTH AND SAFETY

Irritant Avoid contact with skin and eyes. Avoid breathing vapour or sanding dust. When using this product it is recommended that full overalls, gloves, face mask and goggles be worn. Store container in a safe place when not in use. Do not burn container.

WARNING Rags contaminated with this product constitute a fire hazard, soak in water overnight before disposing of.

FIRST AID

EYES Flush with water for at least 15 minutes and seek medical advice.

SKIN Wash contact areas with soap and water. Remove all contaminated clothing, and seek medical advice. Do not scrub.

INHALATION Remove patient from further exposure, and keep patient warm and comfortable.

INGESTION Do not induce vomiting. Rinse mouth with water. Seek medical advice as soon as possible.

TRANSPORTATION AND DISPOSAL

Class	3
Hazchem Code	•3YE; •3Y
UN No	1263
Packing Group No	III
Fire Extinguishing Media	CO ² , Foam, Dry Chemical
Fire Fighting Procedure	Fire fighters should wear self contained breathing apparatus. Fight fire from a protected location as product may explode on heating. The vapours are heavier than air, so may travel along the ground to accumulate in low areas. Fire may flash back along vapour trail, and can also react with oxidising agents. Spills should be cleaned up immediately by using sand or other non-flammable absorbent materials, Ensure material does not enter waterways. Dispose of empty containers in accordance with local by laws.

OTHER INFORMATION

This product may be used for a wide variety of surfaces. If the surface you propose to paint is not referred to, contact Protective Paints Technical Department for classification.

For further technical information please phone 0800 724 684.

RELIABILITY OF INFORMATION

All statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed. Since Protective Paints Ltd has no control over product application, purchasers and users must confirm the suitability of our products under their conditions to meet their own requirements.

ISSUE NUMBER: 933-001 (V2)

ISSUE DATE: 28 August 2013