

933-002

Wooden Slat Oil

PRODUCT DESCRIPTION

Wooden Slat Oil is a blend of natural oils and wax and is designed to enhance the natural colours of wood and improve both water and dirt repellency but not produce a coated look. The product is designed for interior use only.

PHYSICAL PROPERTIES

Colour/Texture	Clear/matt
Volume Solids	34%
Product Density	0.88kg/litre
Drying Time	24 hours
Recoat Time	4 hours
Flash point	50°C

SURFACE PREPARATION

Ensure timber is dry and clean.

APPLICATION DATA

Apply by brush, roller, conventional spray, dipping or rag.

Due to the nature of the product the theoretical spreading rate is determined by the type of timber the product is used on.

HEALTH AND SAFETY

Irritant

Avoid contact with skin and eyes. Avoid breathing vapour or sanding dust. When using this product it is recommended that full overalls, gloves, face mask and goggles be worn. Store container in a safe place when not in use. Do not burn container.

FIRST AID

EYES

Flush with water for at least 15 minutes and seek medical advice.

SKIN

Wash contact areas with soap and water. Remove all contaminated clothing, and seek medical advice. Do not scrub.

INHALATION

Remove patient from further exposure, and keep patient warm and comfortable.

INGESTION

Do not induce vomiting. Rinse mouth with water. Seek medical advice as soon as possible.

TRANSPORTATION AND DISPOSAL

Class	3
Hazchem Code	•3YE; •3Y
UN No	1263
Packing Group No	III
Fire Extinguishing Media	CO ² , Foam, Dry Chemical
Fire Fighting Procedure	Fire fighters should wear self contained breathing apparatus. Fight fire from a protected location as product may explode on heating. The vapours are heavier than air, so may travel along the ground to accumulate in low areas. Fire may flash back along vapour trail, and can also react with oxidising agents. Spills should be cleaned up immediately by using sand or other non-flammable absorbent materials. Ensure material does not enter waterways. Dispose of empty containers in accordance with local by laws.

OTHER INFORMATION

This product may be used for a wide variety of surfaces. If the surface you propose to paint is not referred to, contact Protective Paints Technical Department for classification.

For further technical information please phone 0800 724 684.

RELIABILITY OF INFORMATION

All statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed. Since Protective Paints Ltd has no control over product application, purchasers and users must confirm the suitability of our products under their conditions to meet their own requirements.

ISSUE NUMBER: 933-002

ISSUE DATE: 02 August 2013