

934-000

Rimu Oil Seal

PRODUCT DESCRIPTION

Rimu Oil Seal is a penetrating oil seal/finish designed to provide a hand-rubbed look on rimu and other hard woods. It is suitable for interior use and exhibits very positive drying characteristics. In areas subject to moisture other additional coatings will be required.

PHYSICAL PROPERTIES

Colour/Texture	Clear/Satin
Volume Solids	51.5%
Product Density	0.90kg/litre
Recoat Time	8 hours
Flashpoint	38°C

SURFACE PREPARATION

Ensure surface is clean, sound and dry.

APPLICATION DATA

Apply by Brush, Roller, Conventional Spray, or Rag.

Thinners	Mineral Turps
Theoretical Spreading Rate	6-8 m ² /L depending on surface porosity

HEALTH AND SAFETY

Warning	Rags contaminated with this product constitute a fire hazard, soak in water overnight before disposing of.
Irritant	Avoid contact with skin and eyes. Avoid breathing vapour or sanding dust. When using this product it is recommended that full overalls, gloves, face mask and goggles are worn. Store container in a safe place when not in use. Do not burn container.

FIRST AID

EYES	Flush with water for at least 15 minutes and seek medical advice.
SKIN	Wash contact areas with soap and water. Remove all contaminated clothing, and seek medical advice. Do not scrub.
INHALATION	Remove patient from further exposure, and keep patient warm and comfortable.
INGESTION	Do not induce vomiting. Rinse mouth with water. Seek medical advice as soon as possible.

TRANSPORTATION AND DISPOSAL

Class	3a
Hazchem Code	3 [Y]E
UN No	1263
Packing Group No	II/III
Fire Extinguishing Media	CO ₂ , Foam, Dry Chemical
Fire Fighting Procedure	Fire fighters should wear self contained breathing apparatus. Fight fire from a protected location as product may explode on heating. The vapours are heavier than air, so may travel along the ground to accumulate in low areas. Fire may flash back along vapour trail, and can also react with oxidising agents. Spills should be cleaned up immediately by using sand or other non-flammable absorbent materials. Ensure material does not enter waterways. Dispose of empty containers in accordance with local by laws.

OTHER INFORMATION

This product may be used for a wide variety of surfaces. If the surface you propose to paint is not referred to, contact Protective Paints Technical Department for classification.

For further technical information please phone 0800 724 684.

RELIABILITY OF INFORMATION

All statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed. Since Protective Paints Ltd has no control over product application, purchasers and users must confirm the suitability of our products under their conditions to meet their own requirements.

ISSUE NUMBER: 934-000 (V1)

ISSUE DATE: April 2013