



# PROTECTIVE

PAINTS

Protective Paints Limited, 14B Arwen Place, East Tamaki, PO Box 204293, Highbrook Postal Centre, Manukau 2161  
Ph: (09) 274 5606 Ph: 0800 724 684 Fax: (09) 274 0940 Email: reception@propaints.co.nz Website: www.propaints.co.nz

## A536

### Don't Slip

A hard acrylic polymer designed to be used in a variety of situations such as boat decks, patio decks, steps, concrete and fibrolite decks, ramps and light industrial non-skid flooring situations such as pool surrounds and wet areas.

#### PRODUCT FEATURES

- Very hard acrylic polymer
- Attractive finish
- Effective non-slip coating
- Cost effective
- Can be over-glazed

#### CHECKLIST

Quality	Premium
Int/Ext	Both
Colour	White. Can be tinted to a range of pastel colours. Test and approve colour before you start.
Gloss Level	Eggshell
Wet Areas	Yes
Primer Required	N/A
Wash Up	Water

#### ESTIMATION

Pack Size	1L, 4L
Appearance When Dry	5% gloss at 60°tri gloss meter
Storage Temperature	10°C-50°C
Shelf Life (months)	18
Toxicity	Contains no lead or mercury
Percentage by Weight	62%
Flash point	N/A
Volume solids	48%
Dry film thickness	A minimum working film build of 250 microns is required
Wet film thickness/coat	The application of one coat at 2m <sup>2</sup> /litre rolled out to obtain an effective texture will give an approximate dry film build of 200 microns.
Potlife (@ 25°C)	Single Pack
Mixing	Stir thoroughly with a broad paddle to ensure product is fully incorporated
Spreading Rate	For every 1m <sup>2</sup> apply 0.5 litres i.e. no more than 2m <sup>2</sup> /litre

#### APPLICATION

##### SURFACE PREPARATION

Sand back existing coating to a rough finish then mask area to be coated. Ensure surface is sanded up to masking line. Wash away debris, dirt, dust etc, with a mild detergent solution and rinse with warm water. Remove mould and lichen, dirt, dust etc if applying to concrete surfaces. Remove masking tape when coating has dried by cutting tape edge with a sharp cutting blade. Existing coatings must be sanded back to a dull finish, cleaned and checked to ensure adhesion to substrate is good.

Timber surfaces should be primed with a quality oil based primer. Prime concrete surfaces with a thin coat of Don't Slip diluted 20% with water. Where existing coating is sound and well adhered apply Don't Slip direct to the surface.

## APPLICATION DETAILS

Minimum Steel Temperature	10°C
Maximum Relative Humidity	75%
Application Temperature Range	10°C – 35°C

## METHODS

Brush and roller

(Note: Do not work in direct sunlight. Work small areas at a time. Do not apply coatings if the substrate and surrounding air temperature is less than 10°C. Do not apply in large areas if rain is imminent).

Thinners	Water
Cleaning Solvent	Water
Max. Volume Thinners	Do not thin
Nozzle Orifice	N/A
Fan Angle	N/A
Nozzle Pressure	N/A

## DRYING CHARACTERISTICS

Temperature (deg. C)	10°C	20°C
Touch dry	2 hours	1 hour
Handle dry	4 hours	2 hours
Full cure	16 hours	8 hours

**Overcoating** - May be glazed with a single or two pack polyurethane glaze where additional ease of clean is required. Care must be taken to ensure that the addition of the glaze film does not reduce the Don't Slip effect. Not suitable for vehicular traffic.

Apply in small sections of 1m with a brush. Lay on thickly approximately 0.5 litres per m<sup>2</sup>. Lay off with a goop loop roller. For areas requiring a high level of slip resistance allow the coating to dry slightly before re-rolling. Remove excess material progressively from the roller to ensure effective pattern is obtained.

## HEALTH AND SAFETY

**Irritant** Avoid contact with skin and eyes. Avoid breathing vapour or sanding dust. When using this product it is recommended that full overalls, gloves, face mask and goggles be worn. Store container in a safe place when not in use. Do not burn container.

## FIRST AID

**EYES** Flush with water for at least 15 minutes and seek medical advice.  
**SKIN** Wash contact areas with soap and water. Remove all contaminated clothing, and seek medical advice. Do not scrub.

**INHALATION** Remove patient from further exposure, and keep patient warm and comfortable.

**INGESTION** Do not induce vomiting. Rinse mouth with water. Seek medical advice as soon as possible.

## USE ONLY WITH ADEQUATE VENTILATION

## KEEP OUT OF REACH OF CHILDREN

## TRANSPORTATION AND DISPOSAL

Not Hazchem regulated.

## OTHER INFORMATION

This product may be used for a wide variety of surfaces. If the surface you propose to paint is not referred to, contact Protective Paints Technical Department for classification.

For further technical information please phone 0800 724 684.

**RELIABILITY OF INFORMATION**

All statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed. Since Protective Paints Ltd has no control over product application, purchasers and users must confirm the suitability of our products under their conditions to meet their own requirements.

ISSUE NUMBER: A536 (V2)

ISSUE DATE: 17 September 2013